

## SCRIBE APPLIANCE


Designed for Video Capture

The Seneca Scribe is a purpose-built video capture appliance designed for mission critical performance in a compact 1U short-depth form factor. Powered by the 6th generation Intel® Core™ i7 processor, Scribe combines performance and ease of use with a video capture appliance that can be installed anywhere; including A/V racks, desktops, and podiums.

With optimized system resources and balanced drivers, Scribe guarantees smooth integration and reliability you can depend on. Tested and certified with industry leading video capture software, this appliance is designed for use in distance learning, distance medicine, lecture capture, board rooms, courtrooms as well as many other video capture environments.

### SPECIAL FEATURES AND BENEFITS OF THE SCRIBE

- Convenient single, dual and quad channel HDMI/SDI video capture cards
- Quiet and cool design for low noise threshold during recording and component stability
- 3 year hardware warranty, 24/7 phone and email support, and onsite services available



---

Available in single, dual or quad  
channel HDMI/SDI  
capture card options



The options are endless with the Seneca Scribe appliance from Arrow.

---

# SCRIBE APPLIANCE

P/N: SENECA-SCRIBE-KIT


## SYSTEM

<b>Processor</b>	6th generation Intel® Core™ i7-6700 Processor 3.4GHz 8MB Cache	
<b>Memory</b>	Up to 32GB DDR4 2133MHz SODIMM	
<b>Storage</b>	Up to 2.5TB (1 × mSATA; 2 × 2.5" HDD or SSD)	
<b>Connectivity</b>	<b>LAN 1:</b> Intel® i219-LM Gigabit Ethernet <b>LAN 2:</b> Intel® i210 Gigabit Ethernet	
<b>Graphics</b>	Intel® HD Graphics 530	
<b>Displays Capability</b>	Supports Dual 4K Displays	
<b>USB</b>	4 × USB 3.0 (Rear)	
<b>Expandability</b>	2 × LAN (RJ-45) 1 × Serial (RS-232) 1 × Serial (RS-232/422/485) 2 × DisplayPorts	1 × HDMI 1 × Line Out 1 × Mic In



## MECHANICALS

<b>Power Supply</b>	250W High Efficiency Low Noise PSU	
<b>Thermals</b>	50°C (122°F) Max at full CPU utilization	
<b>Cooling</b>	3 × 40mm low noise fans	
<b>Operating Temperature</b>	0 ~ 50°C (32 ~ 122°F)	
<b>Storage Temperature</b>	-20 ~ 80°C (-4 ~ 176°F)	
<b>Operating Humidity</b>	5 ~ 90% Relative Humidity, Non-condensing	
<b>Storage Humidity</b>	0 ~ 90% Relative Humidity, Non-condensing	
<b>Dimensions (w x h x d)</b>	17.25 × 1.75 × 12 inches / 438 × 45 × 305 millimeters 19 × 1.75 × 12 inches / 483 × 45 × 305 millimeters with handles	
<b>Weight</b>	11 lbs / 5 kg (system) 14 lbs / 6.4 kg (shipping)	



**ARROW**  
Five Years Out

Arrow Electronics, Inc.  
6040 Tarbell Road | Syracuse, NY 13206  
p: 800.227.3432 | www.senecadata.com